24 NRG GROUP

Ceiling Hoist SURGE200

The award winning OT200 Compact Ceiling Hoist is the smallest professional-use patient hoist on the market. The hoist uses a unique gravity powered system and emergency lowering function which does not require tools. The OT200 is a cost effective, flexible solution that can be installed in virtually any setting.

UNIQUE FEATURES

- Compact cassette with no-lights at night
- Gravity powered charging
- No tools emergency lowering
- Low cost of ownership
- Removable padded Spreader Bar
- Retro installations to existing tracks



Gravity Powered - The OT200 has a unique self-charging system that charges the battery automatically whenever in use. It is therefore not reliant upon regular charging, providing a significant cost saving over the life-time of the hoist.

Compact Design

The discreet white motor and track of the OT200 is designed to blend into the surroundings, providing an aesthetically pleasing solution which is available as a 200kg, 250kg or 400kg motor capacity.

Wide Range of Tracking

With the widest range of track options on the market, virtually any layout can be achieved. We understand that the optimum patient handling solutions requires the correct positioning of users.

No-Tools Emergency Lower

If the electric emergency lower can't be used, the OT200 automatically senses a failure and manually winds down the hoist in a safe and controlled manner without carer intervention.

Spreader Bar

The OT200 Ceiling Hoist comes as standard with a modern design spreader bar. The hoist is also available with a manual or powered cradled to suit the user's needs.

Specifications

Model OT200 Compact Ceiling Hoist

Function Patient Lifting, Room-to-Room Transfer, Ideal for Bathrooms, Bedrooms & Home Use

Dimensions Cassette - 303mm x 240mm x 190mm

Weight Capacity 200kg or 250kg

Product Weight 18kg

Options Powered or Manual Tilting Cradle, 2-Point Spreader Bar (Standard), Weigh Scale, Infra-Red

Track Options H-System, Turntable, Gate, 90° Curve, 45° Curve, Room-to-Room, Freestanding Gantry

Track Lengths 2m, 3m, 4.5m, 6m, 8m

Voltage 24Vdc

Lifting Speed 2.5m / min max

Trave Speed 12m / min max

IP Rating IP rating 54

Noise 42dB (A)

Application Nursing Home, Hospital, Domestic, School, Leisure Centre, Physiotherapy

Unique Features Gravity powered charging, No Tools Emergency Down





